

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
ACOUSTIC	QUICKMOUSSE Tweed	FT N°72 V1

This is a core dyed foam PVC acoustic wallcovering, printed using water-based inks, on non-woven backing. Washable and scrubbable, this wallcovering is suitable for intensive use in public buildings. In line with regulations, it has M1 and C s2 d0 fire resistance rating. Quick and easy to hang. Simply paste the wall.

Description

Item codeTWEE 9145NameQuickmousseRangeAcoustic 0.3TypePVC wallcoveringPlainYes - 14 colours

Patterned No

Composition

Type PVC foam

Backing Non-woven backing

 $\begin{tabular}{lll} Weight & 580 g/m^2 \\ Thickness & 1,00 mm \end{tabular}$

Ink Water-based printing inks

Regulations - Environment

Fire rating C s2 d0 / M1 Standard EN 13 501 -1 Acoustics Alpha w = 0.15 / NRC 0.1 Standard EN 20 354 / ASTM-C423-90a

 Light fastness
 ≥ 7
 Standard EN 259

 VOCs
 A+
 ISO 16000

CE marking DOP-CPR-PVCBN-24 / www.texdecor.com Norme EN 15 102

Manufactured by ISO 14001

Component PVC with no phthalate

Care Extra washable - scrubbable Standard EN 259

Packing - Packaging

Size of widths +/- 106 cm Length of roll 30 lm - 15 lm

Partial sale to order No

Dispenser box FSC Certified Cardboard
Box size 110 X 27 X 30 cm for 30 lm

Weight of a roll 19,5 Kg (+/- 10%)

Hanging

Adhesive Ovalit TM (Metylan - Henkel)
Adhesive instructions Apply to the wall, using a roller

Quantity of adhesive +/- 250gr/m²

Match Free match

Hanging direction Invert strips

Seams Overlap seams

Removal Strippable