

### Acoustic vinyl wallcovering – VINACOUSTIC

---

#### Description

This is an acoustic vinyl wallcovering that is dyed in the mass, micro-perforated, printed with water-based ink, coated on an acoustic non-woven backing. Alpha w 0.25 and NRC 0.25. Highly washable and brushable, resistant to impacts and scratches, this wall covering is particularly well-suited for intensive use in commercial and public establishments. In accordance with regulations, it has a M1 and Cs3 d0 fire rating. Quick and easy to hang by simply pasting on the wall and butted seams.

|         |  |
|---------|--|
| Name    | VINACOUSTIC  |
| Type    | Acoustic vinyl wallcovering  |
| Designs | Abaca, Dune, Linen, Melia, Katsura, Katsura Reflect, Tivoli, Urban, Polyform. More than 10 designs and 120 colours available |

---

#### Composition

|           |   |
|-----------|---|
| Type      | Micro-perforated double vinyl coating, impregnated dye-method |
| Backing   | Acoustic non-woven polyester<br>90% recycled material         |
| Weight    | 890 g/m <sup>2</sup>  |
| Thickness | 3,5 mm  |
| Ink       | Water-based printing inks                                     |
| Treatment | Antimicrobial treatment Vinyzene on request                   |

---

#### Regulations - Environment

|                           |  |   |
|---------------------------|--|---|
| Fire rating               | C s3 d0 / M1   | Standard EN 13 501 -1<br>Standard EN 20 354 / |
| Acoustics                 | alpha w 0.25 / NRC 0.25  | ASTM-C423-90a                                 |
| Light fastness            | ≥ 6 (1-8)  | Standard EN 259                               |
| Thermal resistance        | R = 0,08 m <sup>2</sup> K/W  | Standard EN 12 667                            |
| VOCs                      | A+   | ISO 16000                                     |
| CE marking                | DoP-CPR-Vinacoustic / <a href="http://www.texdecor.com">www.texdecor.com</a> | Standard EN 15 102                            |
| Care                      | Extra washable and scrubable   | Standard EN 259                               |
| Use                       | Intensive  | Standard EN 259                               |
| Breaking strength         | Very good : L>35 daN / T >30   | ISO 1421                                      |
| Color fastness to rubbing | Very good : dry 4/5 - wet 4/5 (1-5)  | NF ISO 105                                    |
| Manufactured by           | ISO 14001 / ISO 9002 certification   |   |
| Recycled material         | 26% recycled component   |   |
| Component                 | Phthalate free PVC   |   |
| LCA                       | Environmental & health product declaration                                   | NF EN ISO 14025 / NF EN 15804                 |

---

#### Packing – Packaging

|                          |   |                         |
|--------------------------|---|-------------------------|
| Widths                   | Plain +/- 1,30 m<br>Pattern Polyform +/- 1,25 m               |                         |
| Length of roll           | 25ml - 15ml - 10ml  |                         |
| Partial sale to order    | No  |                         |
| Dispenser box            | Yes   | FSC Certified Cardboard |
| Suspended core packaging | Yes   |                         |
|                          | 1450 X 350 X 350 mm = 25ml ,15ml / 1450 X 215 X 230 mm = 10ml |                         |

Box size  
Weight of a roll 31,22 Kg = 25ml, 19,65 Kg = 15ml, 13,87 Kg = 10ml (+/- 10%)

---

## Hanging operation

|                       |  |
|-----------------------|--|
| Adhesive              | Plain : Ovalit TM & Ovalit F (Metylan - Henkel)<br>Pattern Polyform : Ovalit F (Metylan - Henkel)<br>according to the hanging instructions |
| Adhesive instructions | Apply to the wall, using a roller  |
| Quantity of adhesive  | TM +/- 200 – F +/- 300 g/m <sup>2</sup><br>Plain : free match  |
| Match                 | Pattern : according to the hanging<br>instructions   |
| Seams                 | Butted seams   |
| Removal               | Dampen before stripping  |
| For partitions        | Yes  |
| Hanging instructions  | <a href="http://www.texdecor.com">www.texdecor.com</a>   |
| Demonstration video   | <a href="http://www.texdecor.com">www.texdecor.com</a>   |